



Gerflor®

VIRTUO ADJUST

REMOVABLE VINYL TILES AND PLANKS

MÉMO

BENEFITS

REMOVABLE

NEW TECHNOLOGY **ADJUST**

- Removable
- Precise and easy laying
- Subfloor is clean after removal

THE EASIEST AND FASTEST LAYING SOLUTION

Can be trimmed with an utility knife
No gluing

FOR HOUSEHOLD AND COMMERCIAL USE

European classification 33/42

RESISTANT

0.55 mm wear layer
Shock-resistant varnish
Fiberglass inside
Exclusive looselay construction:
compact and thick for a perfect fit!

IDEAL FOR RENOVATIONS

4 mm thick: doors don't have to be shortened
Direct laying on ceramic
(if joints < 4 mm wide and < 1 mm deep)

REALISTIC

Textured and matt finish surface
4 bevelled edges

SUITABLE FOR HIGH-HUMIDITY ROOMS

Watertight and slip-resistant

EASY TO CLEAN, ECONOMICAL AND ECO-FRIENDLY

Clean with soapy water or neutral detergent



TECHNICAL CHARACTERISTICS

		Planks	Tiles
THICKNESS	mm	4	4
WEAR LAYER THICKNESS	mm	0,55	0,55
WEIGHT	g/m²	7200	7200
DIMENSIONS	cm	121,9 x 18,4	30,5 x 61
AREA PER BOX	m²	1,79	1,86
PLANKS PER BOX	Planks/ Tiles	8	10
SURFACE		Varnished	Varnished
EUROPEAN CLASSIFICATION	Class	33 / 42	33 / 42
FIRE RATING	Class	BflS1	BflS1
SOUND INSULATION	dB	4	4
WATER RESISTANCE		Compatible with wet rooms	
RESIDENTIAL USE GUARANTEE*	year	15	15

* For more details on guarantee, see www.gerflor.com

INSTALLATION TIPS

- **TOOLS REQUIRED:** ruler, utility knife, tape measure.
- **Check** that all planks have the same batch number.
- **Store** the planks in the room, flat and face up, for 24 hours prior to installation.
- **No underlay needed.**
- **Room temperature recommended** during installation: between 15°C and 25°C
- **Temperature range accepted after installation:** minimum 15°C and up to 30°C
Over and above, planks must be glued

SUPPORT TOLERANCE

INSTALLATION POSSIBILITIES ACCORDING TO SUBFLOOR*

HEATED FLOORING

EXPOSURE

Flatness tolerance

Step tolerance

≤ 5 mm under a 2 m ruler

No tolerance

On carpet

On seamless tile (granite-type)

On tile (with joints)

On laminate

On concrete

- If dusty substrates

No Remove subfloor

Yes

Yes if joint < 4 mm wide and < 1 mm deep

No Remove subfloor

Yes

- Use the primer recommended by Gerflor to trap the dust (Gerflor primer not compatible, see gerflor.fr)

On PVC (compact)

On solid or engineered wood floor with ventilated underside

Yes

Yes if subfloor rigid & stable

> 28°C

< 28°C

Reversible

Anhydrite coating

No

Yes

Yes

Yes

Veranda

Skylight

No

Yes if planks are glued

* For more details on installation, see www.gerflor.com

ENVIRONMENT



HEALTH

- Formaldehyde-free
- Lead-free, no heavy metals
- Solvent-free
- No harmful plasticizer
- Low VOC emission

ENVIRONMENT

- 100% recyclable
- Soapy water cleaning