



Gerflor®

VIRTUO LOCK

INTERLOCKING VINYL TILES AND PLANKS

MEMO

BENEFITS

QUICK AND EASY INSTALLATION

Lock system: Proven assembly technology based on laminate parquet flooring

- No gluing
- Can be trimmed with an utility knife

EASY REMOVAL

Planks are easy to remove.
Just one step to change all or part of floor:
ideal for renting!

RESISTANT

0.3 mm wear layer
Shock-resistant varnish
Fiberglass inside

REALISTIC

Textured and matt finish surface
4 bevelled edges

IDEAL FOR RENOVATIONS


4 mm thick: doors don't have to be shortened

SUITABLE FOR HIGH-HUMIDITY ROOMS

Watertight and slip-resistant

EASY TO CLEAN, ECONOMICAL AND ECO-FRIENDLY

Clean with soapy water or neutral detergent



TECHNICAL CHARACTERISTICS

		Planks	Tiles
THICKNESS	mm	4	4
WEAR LAYER THICKNESS	mm	0,3	0,3
WEIGHT	g/m ²	7700	7700
DIMENSIONS	cm	94 x 15	30,3 x 60,7
AREA PER BOX	m ²	1,97	1,84
TILES & PLANKS PER BOX	Planks / Tiles	14	10
SURFACE		Varnished	Varnished
EUROPEAN CLASSIFICATION	Class	23 / 31	23 / 31
FIRE RATING	Class	BflS1	BflS1
SOUND INSULATION	dB	4	4
WATER RESISTANCE		Compatible with wet rooms	
RESIDENTIAL USE GUARANTEE*	Years	12	12

* For more details on guarantee, see www.gerflor.com

INSTALLATION TIPS

- **TOOLS REQUIRED:** ruler, utility knife, tape measure
 - **TIP:** to make life even easier, use a mallet and a tapping bloc
 - **Check** that all planks have the same batch number
 - **Store** the planks in the room, flat and face up, for 24 hours prior to installation
 - **No** underlay needed
 - **Room temperature** recommended during installation: between 15°C and 28°C
 - **Temperature range** accepted after installation: minimum 15°C and up to 30°C
- Over and above, planks must be glued

SUPPORT TOLERANCE

Flatness tolerance
Step tolerance

≤ 5 mm under a 2 m ruler
< 1 mm under a 20 cm ruler

INSTALLATION POSSIBILITIES ACCORDING TO SUBFLOOR*

On carpet
On seamless tile (granite-type)
On tile (with joints)
On laminate
On concrete
On PVC (compact)
On solid or engineered wood floor
with ventilated underside

No Remove subfloor
Yes
No Resurfacing required
No Remove subfloor
Yes
Yes
Yes if subfloor rigid & stable

HEATED FLOORING

> 28° C
< 28°C
Reversible
Anhydrite coating

No
Yes
Yes
Yes

EXPOSURE

Veranda
Skylight

No
Yes if planks are glued

* For more details on installation, see instructions on www.gerflor.com

ENVIRONMENT



HEALTH

- Formaldehyde-free
- Lead-free, no heavy metals
- Solvent-free
- No harmful plasticizer
- Low VOC emission

ENVIRONMENT

- 100% recyclable
- Soapy water cleaning