

DESCRIPTION			
Total thickness	EN 428	mm	2
	ASTM F386-02	inch	0,08
Weight	EN 430	g/sq.m	2630
Width of sheet	EN 426	cm	200
	-	feet - inch	6'6"
Length of sheet	EN 426	lm	20
	-	feet - inch	66'
Coverage / Roll	-	sq.m	40
	-	sq.ft	430,56
CLASSIFICATION			
Norm / Product specification	-	-	EN 649
	ASTM F1913-04	-	Compliant
European classification	EN 685	class	34 - 43
Fire rating	EN 13 501-1	class	Bfl-s1
	ASTM E648-08	class	Class I
	CAN/ULC S 102.2	-	tested in accordance
Static electrical propensity	EN 1815	kV	< 2
PERFORMANCES			
Wear resistance	EN 660.2	mm ³	< 2.0
Wear group	EN 649 - EN 651	-	T
Type binder content	ISO 10581	typ	I
Dimensional stability	EN 434	%	≤ 0.40
Residual indentation (requirement)	EN 433	mm	≤ 0.10
Residual indentation (measure)	EN 433	mm	≈ 0.02
Castor chair test (type W)	EN 425	-	OK
Thermal conductivity	EN 12 524	W/(m.K)	0,25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	Evercare
Chemical products resistance (1)	EN 423	-	OK
Anti-bacterial activity (E. coli - S. aureus - MRSA) (2)	ISO 22196		> 99 % inhibits growth
ENVIRONMENT / INDOOR QUALITY AIR			
TVOC after 28 days	ISO 16000-6	µg/ m ³	< 10
Certification			Floorscore™
CE MARKING			
	EN 14041	  	
			

(1) Regarding the resistance to chemicals, please download the corresponding leaflet from our web-site.

(2) The implementation of an effective cleaning method is the best defence against infection