

# TARALAY IMPRESSION CONTROL

gerflor.com




**PROTECSOL<sup>®</sup>**  
**CONTROL**

New surface treatment

**Gerflor<sup>®</sup>**  
theflooringgroup

# TARALAY IMPRESSION CONTROL

## SAFETY IN WOOD



A stunning collection of remarkable modern and contemporary realistic wood designs suitable for both contract and housing markets. Popular colourways available in light, medium and dark oaks so that you can create an effect, from calming to dramatic.



**Noma** - 0373 Ice



**Ottawa** - 0592 Poplar



**Esterel** - 1713 Frejus\*



**Loft** - 0672 White



**Habana** - 0538 Vinales



**Walnut** - 1314 Brown



**Noma** - 0519 Beige



**Noma** - 0371 Rustic



**Esterel** - 0539 Exotic



**Noma** - 0520 Black



**Habana** - 0522 Trinidad




**Esterel** - 0518 Chocolate

\*Available as Taralay Impression Control only.

Due to printing limitations there may be variations between the colours of the actual flooring and images shown in this document.

# TARALAY IMPRESSION CONTROL

## SAFETY IN DESIGN



An impressive and eye catching collection for inspiring interior spaces that require something unique. New colourways that relate to up and coming trends, striking and distinguished in their own right.



**Cemento** - 0526 Parma



**Urban** - 0038 Pierre



**Fiber** - 0665 Cotton




**Cemento** - 0523 Genova



**Urban** - 0035 Gris



**Fiber** - 0666 Silk




**Cemento** - 0543 Brescia



**Cemento** - 0525 Modena




**Infinity** - 0680 Greige




No plank  
continued  
design




**Cemento** - 0524 Capri



**Cemento** - 0544 Bari



**Infinity** - 0681 Silver\*



No plank  
continued  
design

\*Available as Taralay Impression Control only.

Due to printing limitations there may be variations between the colours of the actual flooring and images shown in this document.

# TARALAY IMPRESSION CONTROL

gerflor.com

Taralay Impression Control is a brand new stunning safety collection of modern and contemporary designs suitable for medium/heavy traffic areas. Ideal for Healthcare, Education, Retail and other Contract Markets.

**TARALAY IMPRESSION CONTROL** is a multi layered vinyl floorcovering with improved slip resistance R11 & HSE 36, available in 2m wide sheet, with a group T wear rating.

**TARALAY IMPRESSION CONTROL** comprises a compacted backing reinforced with a glass fibre and a printed design that is protected by a transparent wear layer (0.70 mm thick).

**TARALAY IMPRESSION CONTROL** offers 8 dB sound insulation and an **indentation resistance of 0.03 mm**.

**TARALAY IMPRESSION CONTROL** is protected by a UV cured surface treatment **ProtecSol® Control** which facilitates ease of maintenance eliminating permanently the need of an acrylic emulsion (metallisation) and improves the slip resistance to reach HSE 36 values.

It does not contain any heavy metals or CMR 1&2 and it is 100% compliant with REACH. The product emission rate of volatile organic compounds is < 70 µg/m³ (TVOC after 28 days – ISO 16000 -6). It is 100% recyclable.

## TARALAY IMPRESSION CONTROL COMPACT

### DESCRIPTION

Total thickness	EN 428	mm	2
	ASTM F386-02	inch	0.08
Wearlayer thickness	EN 429	mm	0.70
	ASTM F410-02	inch	0.03
Weight	EN 430	g/sq.m	2635
	-	lbs/sq.ft	0.54
Width/length of sheet	EN 426	cm / lm	200 / 25
	-	feet - inch	6'6" / 82"

### CLASSIFICATION

Norm / Product specification	-	-	EN 649
	ASTM F1303-04	-	in progress
European classification	EN 685	class	34-43
Fire rating	EN 13501-1	class	Bfl - s1
Static electrical propensity	EN 1815	kV	< 2
Slip resistance: Ramp test	DIN 51 130	class	R11
Slip resistance: Pendulum test <sup>(1)</sup>	BS 7976-2	PTV	> 36
Surface Roughness	µm	Rz	> 20




### PERFORMANCE

Wear resistance	EN 660.2	mm³	≤ 2.0
Wear group	EN 649 - EN 651	-	T
Type binder content	ISO 10582	Typ	I
Dimensional stability	EN 434	%	≤ 0.40
Residual indentation (requirement)	EN 433	mm	≤ 0.10
Residual indentation (average value measured)	EN 433	mm	≈ 0.03
Impact sound insulation	EN ISO 717-2	dB	8
Castor chair test (Type W)	EN 425	-	OK
Thermal conductivity	EN 12 524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	ProtecSol® Control
Chemical products resistance	EN 423	-	OK
Anti-bacterial activity (E. coli - S. aureus - MRSA) <sup>(2)</sup>	ISO 22196	-	> 99 % inhibits growth

### ENVIRONMENT / INDOOR AIR QUALITY

TVOC after 28 days	ISO 16000-6	µg/m³	< 70
Certification			Floorscore™

### CE MARKING

CE	EN 14041	-	  
----	----------	---	---

(1) The RRL pendulum test: wet is expressed as a pendulum test Value (PTV) and a Slip Resistance Value (SRV) to show that the test was carried out using a 4S rubber resistor pad in accordance with HSE guidance (For lifetime sustainable wet resistance, please refer to Tarasafe ranges). (2) The implementation of an effective cleaning method is the best defence against infection.

### INSTALLATION

Laying is the responsibility of the installer. Installation should be made in accordance with installation guidelines supplied and regularly updated by Gerflor's Technical Department. Installation should be carried out in accordance with local standards. Subfloor to be smooth, hard, clean and dry prior to laying. Where applicable the subfloor must incorporate an effective Damp Proof Membrane. The material must be allowed to acclimatise 24 hours prior to installation in a room temperature of between 18-24°C. All seams must be heat welded using Gerflor matching weld rod.

### MAINTENANCE

Maintenance should be carried out regularly to retain the appearance and durability of the floor. The floor covering should be maintained with regular sweeping and damp mopping using a neutral cleaner, or auto scrubber machine with an appropriate pad.

⚠ Rubber leaves indelible stains on vinyl floorings: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide.

Place mats of sufficient length at entrances to reduce outside sources of dirt.

Further installation and maintenance instructions are available on [www.gerflor.com](http://www.gerflor.com)



Committed to sustainable development

**Gerflor®**  
theflooringgroup