

DESCRIPTION			Floorcovering
Total thickness	EN 428	mm	2.00
	ASTM F386-02	inch	0,08
Weight	EN 430	g/sq.m	2750
		lbs/sq.ft	0.56
Width / Length of sheet	EN 426	cm/lm	200 / 20
	-	feet - inch	6'6" / 66'
Coverage / roll	-	m ²	40
	-	sq.feet	430,56
CLASSIFICATION			
Norm / Product specification	-	-	EN 649
	ASTM F1913-04	-	compliant
European classification	EN 685	class	34 - 43
Fire rating	EN 13 501-1	class	Bfl-s1
	ASTM E648-08	class	Class 1
	CAN/ULC 102.2	class	Tested in accordance
Static electrical propensity	EN 1815	kV	< 2
PERFORMANCES			
Wear resistance	EN 660.2	mm ³	≤ 2.0
Wear group	EN 649 - EN 651	-	T
Type binder content	ISO 10581	type	I
Dimensional stability	EN 434	%	≤ 0.40
Residual indentation (requirement)	EN 433	mm	≈ 0.03
Castor chair test (type W)	EN 425	-	OK
Thermal conductivity	EN 12 524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	Evercare™
Anti-bacterial activity (E. coli - S. aureus - MRSA) (1)	ISO 22196	-	> 99.9 % inhibits growth
Chemical products resistance (2)	EN 423	-	OK
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/m ³	< 10
Certification			Floorscore™
CE MARKING			
		EN 14041    	

(1) The implementation of an effective cleaning method is the best defence against infection

(2) Regarding the resistance to chemicals, please download the corresponding leaflet from our website.