

DESCRIPTION

Total thickness	EN 428	mm	2.00
	ASTM F386-02	inch	0.08
Weight	EN 430	g/sq.m	3440
Width of sheet	EN 426	cm	
	-	feet - inch	-
Length of sheet	EN 426	lm	
	-	feet - inch	-
Coverage / roll	-	sq.ft	0
	-	sq.m	0
Tile size	EN 427	mm	608 x 608
Number of tiles per package	-	-	20

CLASSIFICATION

Standard / Product specification		-	EN 649
	ASTM F 1913-04		compliant
European classification	EN 685	class	34 - 43
Fire rating	EN 13501-1	class	B _{fl} -S1
	ASTM E 648	class	Class I
	CAN/ULC S102.2	-	-
Electrical resistance	EN 1081	Ohm	$5 \times 10^4 \leq R \leq 10^6$
	IEC 61340-4-1	Ohm	$R \leq 10^6$
	ANSI / ESD-S7.1	Ohm	$2.5 \times 10^4 \leq R \leq 10^6$
Static electrical propensity	EN 1815	kV	< 2
Static electrical propensity	IEC 61340-4-5	V	< 20
Slip resistance wet: ramp test with oil	DIN 51 130	class	R9

PERFORMANCE

Wear resistance	EN 660.2	mm ³	≤ 4.0
Wear group	EN 649	-	P
Dimensional stability	EN 434	%	≤ 0.25
Residual indentation	EN 433	mm	~ 0.03
Thermal conductivity	EN 12 524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Chemical products resistance	EN 423	-	OK
Anti-bacterial and fungicidal treatment	-	-	OK
TVOC after 28 days	ISO 16000-6	µg/ m ³	< 10

CE MARKING