

DESCRIPTION

Total thickness	EN 428	mm	4.60
	ASTM F386-02	inch	0.18
Thickness of wearlayer	EN 429	mm	0.70
	ASTM F410-02	inch	0.03
Weight	EN 430	g/m ²	5595
Tile size	EN 427	mm	500 x 500
	ASTM F 536	inch	19.685" x 19.685"
Number of tiles per package	-	-	10
Coverage / box	-	sq.m	2.5
	-	sq.ft.	26.9

CLASSIFICATION

Norm / Product specification	-	-	EN 652
	ASTM F 1700- 04	-	Class III Type B
European classification	EN 685	class	34 - 42
Fire rating	EN 13 501-1	class	B _{fl} -s1
	ASTM E648-08	class	1
	CAN/ULC S102.2	-	-
Static electrical propensity	EN 1815	kV	< 2
Slip resistance wet :ramp test with oil	DIN 51130	class	R10

PERFORMANCE

Wear resistance	EN 660.2	mm ³	≤ 2.0
Wear group	EN 652	-	T
Dimensional stability	EN 434	%	≤ 0.25
Residual indentation	EN 433	mm	0.13
Castor chair test (type W)	EN 425	-	OK
Impact sound insulation	EN ISO 717-2	dB	14
Thermal conductivity	EN 12524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	Protecsol®
Chemical products resistance	EN 423	-	OK
Surface treatment	-	-	Protecsol®

ENVIRONMENT / INDOOR AIR QUALITY

TVOC after 28 days	ISO 16000-6	µg/ m ³	< 100
Certification	-	-	Floorscore®

CE MARKING

CE	EN 14041	-	
		-	

