


|                                                             | PRODUCT CHARACTERISTICS    |             |                   |                                                                                                      |
|-------------------------------------------------------------|----------------------------|-------------|-------------------|------------------------------------------------------------------------------------------------------|
|                                                             | Standard                   | Requirement | Unit              | Results                                                                                              |
|                                                             | PRODUCT DESCRIPTION        |             |                   |                                                                                                      |
| Surface treatment                                           | -                          | -           | -                 | Protectsol <sup>TRIPLE ACTION</sup>                                                                  |
| Surface complex                                             | -                          | -           | -                 | D-Max <sup>DURABILITY</sup>                                                                          |
| Foam                                                        | -                          | -           | -                 | CXP <sup>COMFORT</sup> HD                                                                            |
| Thickness                                                   | EN 428                     | -           | mm                | 7 mm                                                                                                 |
| Weight                                                      | EN 430                     | -           | kg/m <sup>2</sup> | 4,6                                                                                                  |
| Length                                                      | EN 426                     | -           | lm                | 26.4 max                                                                                             |
| Width                                                       | EN 426                     | -           | lm                | 1,5                                                                                                  |
| Impact Protection Index                                     | AC- P90-205                | -           | %                 | <b>IPI = 73%</b>                                                                                     |
|                                                             | SPORT PROPERTIES           |             |                   |                                                                                                      |
| Shock absorption                                            | EN 14808                   | ≥ 25        | %                 | P1                                                                                                   |
| Vertical deformation                                        | EN 14809                   | ≤ 3.5       | mm                | ≤ 2                                                                                                  |
| Energy return                                               | NF P 90 203                | ≥ 0.31      | m/s               | ≥ 0.31                                                                                               |
| Sliding coefficient                                         | EN 13036-4                 | 80 to 110   | -                 | 80 - 110                                                                                             |
| Ball bounce                                                 | EN 12235                   | ≥ 90        | %                 | ≥ 90                                                                                                 |
| Ball speed                                                  | UEFA                       | 50 to 65    | cm                | -                                                                                                    |
|                                                             | ITF                        | -           | -                 | -                                                                                                    |
|                                                             | TECHNICAL CHARACTERISTICS  |             |                   |                                                                                                      |
| Abrasion resistance                                         | EN ISO 5470-1              | ≤ 1000      | mg                | ≤ 350                                                                                                |
| Impact resistance                                           | EN 1517                    | ≥ 8         | N/m               | ≥ 8                                                                                                  |
| Indentation resistance                                      | EN 1516                    | ≤ 0.5       | mm                | ≤ 0.5                                                                                                |
|                                                             | CLASSIFICATION             |             |                   |                                                                                                      |
| Fire                                                        | EN 13501-1                 | -           | -                 | Cir-s1                                                                                               |
| Anti-bacterial activity<br>(E. coli - S. aureus - MRSA) (3) | ISO 22196                  | -           | -                 | > 99.9 %<br>inhibits growth                                                                          |
|                                                             | DECLARATION OF PERFORMANCE |             |                   |                                                                                                      |
| CE                                                          | DOP n°xxx                  | -           | -                 | Fire<br>Shock Absorption<br>Sliding Coefficient<br>Abrasion Resistance<br>Resistance to rolling load |

|                                                                                                      | INSTALLATION METHODS              |      |                                                |
|------------------------------------------------------------------------------------------------------|-----------------------------------|------|------------------------------------------------|
|                                                                                                      | Gerflor's recommendation          | Unit | Results                                        |
| Glued installation: "Original"                                                                       | Level of dampness of the subfloor | %    | RH < 80% (BS 8203) or<br>< 4.5% humidity (CCM) |
| Installation on Isolport: "Flexible"                                                                 |                                   | %    | RH < 80% (BS 8203) or<br>< 7.0% humidity (CCM) |
| Dry-Text™ System  |                                   | %    | No limit (no dripping water on the slab)       |

| COLOUR RANGE                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                          |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
|  <p>6381 Maple Design   6375 Oak Design   6211 Gold   6038 Terracotta   6159 Pink   6146 Coral</p> <p>6180 Red   6559 Spring   6557 Forest   6570 Mint Green   2404 London Light Blue   6445 Lagoon   6430 Blue</p> <p>6431 Teal   6758 Silver Gray   6873 Anthracite   3764 Taupe   6347 Beige   6830 Black</p> <p>Standard roll 20.5 ml</p> | <p>TARAFLEX™ SPORT M EVOLUTION</p>  |

(3) The implementation of an effective cleaning method is the best defence against infection

