

DESCRIPTION

Total thickness	EN 428	mm	6.00
	ASTM F386-02	inch	0.24
Thickness of wearlayer	EN 429	mm	2
	ASTM F410-02	inch	0.08
Weight	EN 430	g/m ²	9240
Tile size	EN 427	mm	635 x 635
	ASTM F 536	inch	25" x 25"

CLASSIFICATION

Norm / Product specification	-	-	EN 649
	ASTM F 1700- 04	-	-
European classification	EN 685	class	34 - 43
Fire rating	EN 13 501-1	class	B _{fl} -s1
	ASTM E648-08	class	class I
	CAN/ULC S102.2	-	-
Static electrical propensity	EN 1815	kV	< 2
Slip resistance wet: ramp test with oil	DIN 51 130	class	R10

PERFORMANCE

Wear resistance	EN 660.2	mm ³	≤ 2
Wear group	EN 649	-	T
Type Binder content	ISO 10582	type	II
Dimensional stability	EN 434	%	≤ 0.25
Shore hardness	EN ISO 868	H _D	≥ 50
Castor chair test (type W)	EN 425	-	OK
Thermal conductivity	EN 12524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Chemical products resistance	EN 423	-	OK
Surface treatment	-	-	PUR+
TVOC after 28 days	ISO 16000-6	µg/ m ³	< 100

CE MARKING

	EN 14041	-	  
		-	